

Cited Ref. 4
(ABSTRACTS)

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 59-079002

(43)Date of publication of application : 08.05.1984

(51)Int.Cl.

F01C 9/00

F02B 53/00

(21)Application number : 57-187503

(71)Applicant : SUZUKI AKIRA

(22)Date of filing : 27.10.1982

(72)Inventor : SUZUKI AKIRA

(54) PENDULUM TYPE POWER DEVICE

(57)Abstract

PURPOSE: To obtain a wide pressure receiving area and to make it possible to generate a high output through a low pressure power source by a method wherein an oscillating plate is arranged within a fan-shaped cylinder so as to oscillate about a shaft as a fulcrum point and a connecting rod is connected to the oscillating plate.

CONSTITUTION: An air tight ring 2 is arranged around the oscillating plate 1 and the shaft 3 is provided at the lower end of the oscillating plate 1. Further, the oscillating plate 1 is arranged in the fan-shaped cylinder 4 in such a manner that the plate 1 oscillates right and left about the fulcrum point shaft 3. In addition, a crank 5 is arranged on the side wall of the air cylinder 4 and the connecting rod 6 is connected to the oscillating plate 1. In the titled device, when a gas within the cylinder 4 explodes, the oscillating plate 1 rotates about the shaft 3 due to the pressure of the gas so that the connecting rod 6 is thrust by the plate 1 to thereby rotate the crank 5. In this case, the oscillating plate 1 converts the gas pressure into circular motions which are transmitted to the crank 5 and therefore, the entire connecting rod moves circularly to thrust the crank 5 with the result that the range of the dead center of the crank becomes smaller than in the case of a piston and the transmitting efficiency is improved.

